

Declaration of Performance

No: LT21000RZZ1000RZZ



ŞİŞECAM
LAMINATED GLASS

clear Float Glass + Transparent PVB + clear Float Glass 1010.2

2007

EN 14449 : 2007

Notified Body: 1750

Laminated safety glass, intended to be used in buildings and construction works


Characteristics	AVCP System	Performance
Safety in the case of fire:		
Resistance to fire (13501-2)	1	NPD
Reaction to fire (13501-1)	3.4	NPD
External fire behaviour (EN 13501-5)	3.4	NPD
Safety in use:		
Bullet resistance (EN 1063)	1	NPD
Explosion resistance (EN 13541)	1	NPD
Burglar resistance (EN 356)	3	P2A
Pendulum body impact resistance (EN 12600)	3	1 (B) 1
Resistance against sudden temperature changes and temperature differentials	4	NPD
Wind, snow, permanent and imposed load resistance of the glass unit	4	1010.2
Protection against noise:		
Direct airborne sound reduction (EN 12758)	4	37 (-1; -3) dB
Thermal properties:		
U-value (EN 673)	3	5.3 W/(m ² K)
Normal emissivity (EN 12898)	3	0.89
Radiation properties (EN 410):		
Light transmission	3	0.82
Light reflection outdoor	3	0.08
Light reflection indoor	3	0.08
Solar energy characteristics (EN 410):		
Solar transmission	3	0.58
Solar reflection outdoor	3	0.06
Solar reflection indoor	3	0.06

NPD: No performance determined.

The performance of the product identified is in conformity with the declared performance above.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Name and function	Place and date of issue	Signature
Gökhan Atikkan Basic Glass Production Director	1 July 2013 İstanbul	

TRAKYA CAM SANAYİİ A.Ş.

ŞİŞECAM HEADQUARTERS

İçmeler Mahallesi, D-100 Karayolu Caddesi, No:44A
34947 Tuzla/İstanbul - TURKEY

T (+90)850 206 50 50

F (+90)850 208 40 40

sisecamduzcam.com